

# SAFETY DATA SHEET

## Asterene HHM 5202 Polyethylene

Version 1.0

Revision Date 01.08.2025

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Product information

Product Name : Asterene HHM 5202 Polyethylene  
Material : 1018763, 1018041, 1018037, 1018767, 1018764, 1019865,  
1019867, 1019333, 1019328, 1019330, 1019331, 1018766,  
1017236, 1110384, 1019868, 1019870, 1018768, 1025097,  
1018765, 1017232

**Company** : Aster Polymer Solutions Pte. Ltd.  
460 Alexandra Road,  
mTower #07-01  
Singapore 119963

Telephone : +65 6263 5100

Local : See Company Address

#### Emergency telephone:

##### Transport:

CHEMTREC 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)

China: +86 532-83889090

Mexico CHEMTREC +52 5 8526 9430

South America SOS-Cotec Inside Brazil: 0800 892 0479 (Toll Free) Outside Brazil: +55 21 3958-1449 (Rio De Janeiro), +55 11 4349-1359 (Sao Paulo)

Argentina: +54 11 5983-9431

EUROPE: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)

Austria: +43 1 3649237, 0800 293702 (Toll Free)

Belgium: +32 2 808 32 37

Bulgaria: +359 32 570 104

Croatia: +385 1 7776 920

Cyprus: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)

Czech Republic: +420 228 880 039

Denmark: +45 69 91 85 73

Estonia: +372 668 1294

Finland: +358 9 42725036

France: +33 9 75 18 14 07

Germany: 0800 1817059 (Toll Free)

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

Greece: +30 21 1176 8478  
Hungary: +36 1 808 8425  
Iceland: +354 539 0655  
Ireland: +353 1 901 4670  
Italy: +39 02 4555 7031, 800 789 767 (Toll Free)  
Latvia: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)  
Liechtenstein: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)  
Lithuania: +3705 214 0238  
Luxembourg: +352 20 20 24 16  
Malta: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)  
The Netherlands: +31 85 888 0596  
Norway: 1-800-424-9300 (Toll Free) or +1-703-527-3887 (int'l)  
Poland: +48 22 398 80 29  
Portugal: +351 308 801 773  
Romania: +40 376 300 026  
Slovakia: +4212 330 579 72  
Slovenia: +386 1 888 80 16  
Spain: +34-931768545, 900 868 538 (Toll Free)  
Sweden: +46 8 525 034 03

**MEDICAL APPLICATION CAUTION:** Do not use this material in medical applications involving permanent implantation in the human body or permanent contact with internal body fluids or tissues fluids or tissues.

Do not use this material in medical applications involving brief or temporary implantation in the human body or contact with internal body fluids or tissues unless the material has been provided directly from Aster Polymer Solutions Pte. Ltd. or its legal affiliates under an agreement which expressly acknowledges the contemplated use.

Aster Polymer Solutions Pte. Ltd. and its legal affiliates makes no representation, promise, express warranty or implied warranty concerning the suitability of this material for use in implantation in the human body or in contact with internal body fluids or tissues.

**SECTION 2: Hazards identification**

**Classification of the substance or mixture**  
**SS 586 : Part 2: Specification for Hazard Communication for Hazardous Chemicals and Dangerous Goods, Part 2 : Globally harmonized system of classification and labelling of chemicals - Singapore's adaptations**

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

**Classification**

Not a hazardous substance or mixture.

**Labeling**

Not a hazardous substance or mixture.

**SECTION 3: Composition/information on ingredients**

| Chemical name                 | CAS-No. / EINECS-No. | Concentration [wt%] |
|-------------------------------|----------------------|---------------------|
| Polyethylene Hexene Copolymer | 25213-02-9           | 99 - 100            |

Contains no hazardous ingredients according to GHS.

**SECTION 4: First aid measures**

- If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If symptoms persist, call a physician.
- In case of skin contact : If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Do not induce vomiting without medical advice.

**SECTION 5: Firefighting measures**

- Flash point : No data available
- Autoignition temperature : No data available
- Suitable extinguishing media : Water. Water mist. Dry chemical. Carbon dioxide (CO<sub>2</sub>). Foam. If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer. Avoid the use of straight streams that may create a dust cloud and the risk of a dust explosion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire fighting : Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
- Special protective equipment for fire-fighters : Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

- Further information : This material will burn although it is not easily ignited.
- Fire and explosion protection : Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Hazardous decomposition products : Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.

**SECTION 6: Accidental release measures**

- Personal precautions : Sweep up to prevent slipping hazard. Avoid breathing dust. Avoid dust formation.
- Environmental precautions : Do not contaminate surface water. Prevent product from entering drains.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum.
- Additional advice : Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).

**SECTION 7: Handling and storage****Handling**

- Advice on safe handling : Use good housekeeping for safe handling of the product. Keep out of water sources and sewers. Spilled pellets may create a slipping hazard. Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. At elevated temperatures (>350°F, >177°C), polyethylene can release vapors and gases, which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. These substances may include acetaldehyde, acetone, acetic acid, formic acid, formaldehyde and acrolein. Based on animal data and limited epidemiological evidence, formaldehyde has been listed as a carcinogen. Following all recommendations within this SDS should minimize exposure to thermal processing emissions.
- Advice on protection against fire and explosion : Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

**Storage**

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

Requirements for storage areas and containers : Keep in a dry place. Keep in a well-ventilated place.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

**SECTION 8: Exposure controls/personal protection****Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

**Personal protective equipment**

Respiratory protection : No respiratory protection is normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear an appropriate respirator. Use the following elements for air-purifying respirators: Organic Vapor and Formaldehyde. A positive pressure, air-supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.  
Dust safety masks are recommended when the dust concentration is excessive.

Eye protection : Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.

Skin and body protection : At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.

**SECTION 9: Physical and chemical properties****Information on basic physical and chemical properties****Appearance**

Form : Pellets  
Physical state : solid  
Color : Opaque  
Odor : Mild to no odor  
Odor Threshold : No data available

**Safety data**

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

|   |   |
|---|---|
| Flash point                             | : No data available   |
| Lower explosion limit                   | : Not applicable  |
| Upper explosion limit                   | : Not applicable  |
| Autoignition temperature                | : No data available   |
| Thermal decomposition                   | : Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.  |
| pH                                      | : Not applicable  |
| Melting point/ range                    | : 90-140°C (194-284°F)  |
| Freezing point                          | Not applicable  |
| Initial boiling point and boiling range | : Not applicable  |
| Vapor pressure                          | : Not applicable  |
| Relative density                        | : Not applicable  |
| Density                                 | : 0.91 - 0.97 g/cm <sup>3</sup><br>Please refer to the Technical Data Sheet (TDS) for more detailed information relating to the nominal physical properties, including density, of this polyethylene resin grade. |
| Water solubility                        | : negligible  |
| Partition coefficient: n-octanol/water  | : No data available   |
| Solubility in other solvents            | : No data available   |
| Viscosity, dynamic                      | : Not applicable  |
| Viscosity, kinematic                    | : Not applicable  |
| Relative vapor density                  | : Not applicable  |
| Evaporation rate                        | : Not applicable  |

**SECTION 10: Stability and reactivity**

|                   |  |
|-------------------|--|
| <b>Reactivity</b> | : This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure. |
|-------------------|--|

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

- Chemical stability** : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- Possibility of hazardous reactions**
- Conditions to avoid** : Avoid prolonged storage at elevated temperature.
- Materials to avoid** : Avoid contact with strong oxidizing agents.
- Thermal decomposition** : Low molecular weight hydrocarbons, alcohols, aldehydes, acids and ketones can be formed during thermal processing.
- Hazardous decomposition products** : Normal combustion forms carbon dioxide, water vapor and may produce carbon monoxide, other hydrocarbons and hydrocarbon oxidation products (ketones, aldehydes, organic acids) depending on temperature and air availability. Incomplete combustion can also produce formaldehyde.
- Other data** : No decomposition if stored and applied as directed.

**SECTION 11: Toxicological information****Asterene HHM 5202 Polyethylene****Acute oral toxicity** : Presumed Not Toxic**Asterene HHM 5202 Polyethylene****Acute inhalation toxicity** : Presumed Not Toxic**Asterene HHM 5202 Polyethylene****Acute dermal toxicity** : Presumed Not Toxic**Asterene HHM 5202 Polyethylene****Skin irritation** : No skin irritation**Asterene HHM 5202 Polyethylene****Eye irritation** : No eye irritation**Asterene HHM 5202 Polyethylene****Sensitization** : Did not cause sensitization on laboratory animals.**Asterene HHM 5202 Polyethylene**

**Further information** : This product contains POLYMERIZED OLEFINS. During thermal processing (>350°F, >177°C) polyolefins can release vapors and gases (aldehydes, ketones and organic acids) which are irritating to the mucous membranes of the eyes, mouth, throat, and lungs. Generally these irritant effects are all transitory. However, prolonged exposure to irritating off-gases can lead to pulmonary edema. Formaldehyde (an aldehyde) has been classified as a carcinogen based on animal data and limited epidemiological evidence.

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

**SECTION 12: Ecological information****Ecotoxicity effects**

Biodegradability : This material is not expected to be readily biodegradable.

Elimination information (persistence and degradability)

Bioaccumulation : Does not bioaccumulate.

Mobility : The product is insoluble and floats on water.

Additional ecological information : This material is not expected to be harmful to aquatic organisms., Fish or birds may eat pellets which may obstruct their digestive tracts.

**Ecotoxicology Assessment****SECTION 13: Disposal considerations**

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

**SECTION 14: Transport information**

**The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).**

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

**US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)**

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)**

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

**Maritime transport in bulk according to IMO instruments**

**SECTION 15: Regulatory information****Notification status**

|                                     |   |  |
|-------------------------------------|---|--|
| Europe REACH                        | : | On the inventory, or in compliance with the inventory  |
| Switzerland CH INV                  | : | On the inventory, or in compliance with the inventory  |
| United States of America (USA) TSCA | : | On or in compliance with the active portion of the TSCA inventory  |
| Canada DSL                          | : | All components of this product are on the Canadian DSL   |
| Australia AIC                       | : | On the inventory, or in compliance with the inventory  |
| New Zealand NZIoC                   | : | On the inventory, or in compliance with the inventory  |
| Japan ENCS                          | : | On the inventory, or in compliance with the inventory  |
| Korea KECI                          | : | A substance(s) in this product was not registered, notified to be registered, or exempted from registration by Aster Polymer Solutions according to K-REACH regulations.<br>Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s). |
| Philippines PICCS                   | : | On the inventory, or in compliance with the inventory  |
| China IECSC                         | : | On the inventory, or in compliance with the inventory  |
| Taiwan TCSI                         | : | On the inventory, or in compliance with the inventory  |

**SECTION 16: Other information****Further information**

**Asterene HHM 5202 Polyethylene**

Version 1.0

Revision Date 01.08.2025

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Key or legend to abbreviations and acronyms used in the safety data sheet**

|        |  |       |  |
|--------|--|-------|--|
| ACGIH  | American Conference of Government Industrial Hygienists  | LD50  | Lethal Dose 50%  |
| AIRC   | Australian Inventory of Industrial Chemicals             | LOAEL | Lowest Observed Adverse Effect Level   |
| DSL    | Canada, Domestic Substances List                         | NFPA  | National Fire Protection Agency  |
| NDSL   | Canada, Non-Domestic Substances List                     | NIOSH | National Institute for Occupational Safety & Health                                  |
| CNS    | Central Nervous System                                   | NTP   | National Toxicology Program  |
| CAS    | Chemical Abstract Service                                | NZIoC | New Zealand Inventory of Chemicals   |
| EC50   | Effective Concentration                                  | NOAEL | No Observable Adverse Effect Level   |
| EC50   | Effective Concentration 50%                              | NOEC  | No Observed Effect Concentration   |
| EGEST  | EOSCA Generic Exposure Scenario Tool                     | OSHA  | Occupational Safety & Health Administration  |
| EOSCA  | European Oilfield Specialty Chemicals Association        | PEL   | Permissible Exposure Limit   |
| EINECS | European Inventory of Existing Chemical Substances       | PICCS | Philippines Inventory of Commercial Chemical Substances                              |
| MAK    | Germany Maximum Concentration Values                     | PRNT  | Presumed Not Toxic   |
| GHS    | Globally Harmonized System                               | RCRA  | Resource Conservation Recovery Act   |
| >=     | Greater Than or Equal To                                 | STEL  | Short-term Exposure Limit  |
| IC50   | Inhibition Concentration 50%                             | SARA  | Superfund Amendments and Reauthorization Act.  |
| IARC   | International Agency for Research on Cancer              | TLV   | Threshold Limit Value  |
| IECSC  | Inventory of Existing Chemical Substances in China       | TWA   | Time Weighted Average  |
| ENCS   | Japan, Inventory of Existing and New Chemical Substances | TSCA  | Toxic Substance Control Act  |
| KECI   | Korea, Existing Chemical Inventory                       | UVCB  | Unknown or Variable Composition, Complex Reaction Products, and Biological Materials |
| <=     | Less Than or Equal To                                    | WHMIS | Workplace Hazardous Materials Information System                                     |
| LC50   | Lethal Concentration 50%                                 | ATE   | Acute toxicity estimate  |